

Galvanized High Utilization Pallet Vertical Vna Racking For Customized Warehouse Storage

Basic Information





Product Specification

QF-VNA

Steel

Rack

Fixed

5-15m

Open

Pallet Racking

1000-4500kg

Conventional Common Use

Customized

20 Days

Q235B

- Model NO.:
- Material:
- Structure:
- Type:
- Mobility:
- Height:
- Weight:
- Closed:
- Development:
- Serviceability:
- Color:
- Lead Time:
- Raw Material:
- Surface Treatment: Galvanized/Powder Coating
- Transport Package: Standard Export Packing



More Images









Product Description



Source Manufacturer & Free Customized Design & One Stop Service

Product Description

VNA(Very Narrow Aisle) rack:

Very narrow aisle pallet rack mainly used with the most advantage three ways forklift, occupying small aisle, saving space of warehouse, can store and pick up products quickly so as to cut down the operating cost, particularly suitable for logistic center less than 15 m high.



Comparing with the conventional pallet rack, VNA rack aisle is much narrower, ordinarily 1600-2000 mm, the space utilization rate will increase about 20%.



Very Narrow Aisle Rack Configuration



Guide rails should be installed on both sides of aisle for the three-way forklift running.





Style	Warehouse Storage Pallet Rack
Dimension	Standard Pallet: 1200*800(F) / 1200*1000(F) / 1100*1100(F) / 1066(F)*1220 Depth 1000MM / 900MM / 1020MM Width: 2700MM / 2300MM / 2500MM / 2432MM Height: pitch is adjusted by increments of 75mm For Customized case, please contact us directly
Beam	Height:80~160mm; Width:45mm/50mm; Thickness:1.5~2.5mm
Upright	80*60; 90*60; 90*70; 90*75; 100*67; 100*70; 100*75; 120*75; 120*87mm, Thickness:1.5~3.0mm
Bearing Capacity	5000KG per level max ; 1500KG per pallet max

Detailed Photos



Advantages

- 1) This storage racking makes optimum use of floor area and roof height by providing high density storage
- 2) Pallets can be located, accessed and moved individually
- 3) The height between levels can be easily adjusted by 50 mm pitch interval
- 4) Strength and rigidity prevents compression damage to goods.
- 5) Bottom level of pallets can be stored on the floor, lowering structure costs.
- 6) Rich accessories: upright protector, guide rail, frame barrier, row spacer, wire deckings, steel shelf, etc

Upright



upright:80*60 pitch:50&75mm hole:diamond upright:90+70 pitch:50&75mm hole:diamond

upright:90+67

pitch:50&75mm

hole:square

upright:100+70 pitch:75mm hole:diamond

100

upright:100+67

pitch:75mm

hole:square

upright:120*95 pitch:75mm hole:diamond

pitch:50.8mm

hole:teardrop

upright:140+95 pitch:75mm hole:diamond



upright:76.2*76.2 pitch:50.8mm hole:teardrop

<u>Beam</u>

upright:85*67 pitch:50&75mm

hole:square



Client Site







Q: What parameters do I need to provide for an accurate guotation?

1) Quantity(set)

2) Size: Length*Width*Height (mm) or samples or technical drawings

3) Load capacity per layer(kg)

- 4) Number of layers
- Q: What is the material being used for your products?

A: Mild steel Q235.

Q: I don't have drawing or picture available for the products, could you design it for me? A: Yes, we can make the best suitable design for you but need to know more details.

Q: Do I get any guarantee from your company?

A: 3~10 years warranty

Q: How do you make our business long-term and good relationship?

A: Quality makes trust and reputation, plus competitive price to ensure our customers benefit ;

More Choice



Add: #739 Dixiu Road Jiangning District Nanjing China